

MATERIAL SAFETY DATA SHEET

PAGE 1
SECTION I

MANUFACTURER' S NAME: Moreau Marketing & Sales
485 Glenn Link Road Lexington NC 27295
EMERGENCY TELEPHONE NUMBER: 336-764-5232

TRADE NAME: Silver Plated Glass Filled Silicone Adhesive
Series 030

CHEMICAL NAME: Same

CHEMICAL FAMILY: POLY-SILOXANE
DATE PREPARED: 5/14/07
MSDS COORDINATOR: Robert Moreau

SECTION II
HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	CAS#	TLV	PEL	%
SILICA, AMORPHOUS	7631-86-9	10 MC/M3	15 MG/M3	4.030
SILICA, QUARTZ	14808-60-7	0.1 MG/M3	0.1 MG/M3	3.879
DIMETHYL, METHYL HYDROGEN SILOXANE COPOLYMER	68037-59-2	NOT DET.	NOT DET.	1.750
POLYDIMETHYL, METHYL VINYL SILOXANE DIMEVI TERMINATED	68083181	NOT DET.	NOT DET.	5.358
SILVER	7440-22-4	10mg/m3	.01mg/m3	3.200
SODA LIME GLASS	65997-17-3	10mg/m3	NL	50.100
C5-C6-RICH HYDROCARBONS	068476506	0.1 MG/M3	0.1 MG/M3	0.020
HEXAMETHYLDISILOXANE	000107460	NOT DET.	NOT DET.	2.200

THE ABOVE INFORMATION IS DEEMED RELIABLE AS FAR AS OUR SUPPLIERS POSITION ON REPORTING CONCENTRATIONS OF HAZARDOUS COMPONENTS IN THE MATERIALS THEY SUPPLY. THIS DATA IS OFFERED IN GOOD FAITH AND IS NOT INTENDED TO BE USED FOR PRODUCT SPECIFICATIONS.

SECTION III
PHYSICAL AND CHEMICAL CHARACTERISTICS

BOILING POINT	N/A
VAPOR DENSITY	N/A
MELTING POINT	N/A
APPEARANCE AND ODOR	GUM-LITTLE ODOR
SPECIFIC GRAVITY	2.03
VAPOR PRESSURE	N/A
SOLUBILITY IN WATER	NILL
EVAPORATION POINT	NONE

SECTION IV
FIRE AND EXPLOSION DATA

FLASH POINT : CLOSED CUP ABOVE 200 DEF.F. (93 DEG.C.)
FLAMMABLE LIMITS : NOT DETERMINED
EXTINGUISHING MEDIA WATER, WATER-FOG, CO2, DRY CHEMICAL, OR FOAM SPECIAL
FIRE FIGHTING PROCEDURES SELF-CONTAINED BREATHING APPARATUS AND
PROTECTIVE CLOTHING SHOULD BE WORN IN FIRES INVOLVING
THESE CHEMICALS.
UNUSUAL FIRE AND EXPLOSION HAZARDS : NONE KNOWN.

SECTION V

REACTIVITY DATA

STABILITY : STABLE

INCOMPATIBILITY : KEEP AWAY FROM STRONG OXIDIZING
AGENTS

HAZARDOUS DECOMPOSITION OR BYPRODUCTS : SILICONE
DIOXIDE, CARBON DIOXIDE AND TRACE
AMOUNTS OF INCOMPLETELY BURNED CARBON

PRODUCTS.

HAZARDOUS POLYMERIZATION : WILL NOT OCCUR.

SECTION VI
HEALTH HAZARD DATA

ROUTE OF ENTRY

EYE : MAY CAUSE TEMPORARY EYE DISCOMFORT

SKIN : PROLONGED EXPOSURE SHOULD BE AVOIDED

ORAL : AMOUNTS TRANSFERED TO THE MOUTH BY
FINGERS, ETC., DURING NORMAL
OPERATIONS SHOULD NOT CAUSE INJURY.

HEALTH HAZARDS : NO KNOWN ADVERSE CHRONIC HEALTH
EFFECTS, BUT UNNECESSARY EXPOSURE TO
ANY CHEMICAL SHOULD BE AVOIDED.

CARCINOGENICITY

CAUTIONS : THESE PRECAUTIONS ARE FOR ROOM TEMPERATURE
HANDLING, USE AT ELEVATED TEMPERATURES, OR
AEROSOL/SPRAY APPLICATIONS, MAY REQUIRE
ADDED PRECAUTIONS.

- GOOD PRACTICE REQUIRES THAT CROSS AMOUNTS OF ANY CHEMICAL BE REMOVED FROM SKIN AS SOON AS PRACTICAL, ESPECIALLY BEFORE EATING OR SMOKING.
- THIS PRODUCT, AS WITH ANY CHEMICAL, MAY AGGREGATE ALLERGIC CONDITIONS ON CERTAIN PEOPLE.

SECTION VII
PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE OF
RELEASED OR SPILLED MATERIAL : REMOVE MATERIAL AND USE
ABSORBANT TO PICK UP
OIL-LIKE RESIDUES.

WASTE DISPOSAL METHOD : FOLLOW ALL LOCAL AND FEDERAL
REGULATIONS CONCERNING WASTE
HANDLING.

PROTECTIVE EQUIPMENT : EYES USE SAFETY GLASSES.

INHALATION : PROCESSING FUMES SHOULD BE REMOVED
THROUGH FORCED
VENTILATION FROM WORKING AREA.

SKIN : USE PLASTIC GLOVES WHEN POSSIBLE. WASH HANDS
WITH SOAP AND WATER AT MEAL
TIME AND END OF SHIFT.

SECTION VIII
CONTROL MEASURES NJ

VENTILATION : USE MECHANICAL VENTILATION DURING MOLDING AND POSTCURING.
POSTCURING IN A CLOSED OVEN MAY LIBERATE EXPLOSIVE CONCENTRATIONS OF
GAS. USE PROPERLY DESIGNED EQUIPMENT.

SECTION IX
SPECIAL PRECAUTIONS

UNDER NORMAL PROCESSING CONDITIONS, CRYSTALLINE SILICA IS CONSIDERED TO BE SAFE THROUGH ENCAPSULATION. AVOID PROCESSING CONDITIONS THAT RELEASE SMALL PARTICLES OF MATERIALS (10 MICROMETERS OR LESS). IF NECESSARY, USE NIOSHA/MSHA APPROVED RESPIRATORY EQUIPMENT.

PRODUCT MAY FORM FORMALDEHYDE VAPORS AT TEMPERATURES ABOVE 300F (150C) IN THE PRESENCE OF AIR. FORMALHYDE IS A POTENTIAL CANCER HAZARD AND A KNOWN SKIN AND RESPIRATORY SENSITIZER. VAPORS IRRITATE EYES, NOSE, AND THROAT. SAFE HANDLING CONDITIONS MAY BE MAINTAINED BY KEEPING VAPOR CONCENTRATIONS WITHIN OSHA PERMISSIBLE EXPOSURE LIMITS FOR FORMALDEHYDE.

THESE DATA ARE OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EITHER EXPRESSED OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE AND DETERMINE WHETHER THEY ARE APPROPRIATE.

SECTION X
PREVAILING INGREDIENTS

INGREDIENT	CAS#	TLV	PEL	%
SILICA, AMORPHOUS	7631-86-9	10 MC/M3	15 MG/M3	4.030
SILICA, QUARTZ	14808-60-7	0.1 MG/M3	0.1 MG/M3	3.879
DIMETHYL, METHYL HYDROXY-TERMINATED	68037-59-2	NOT DET.	NOT DET.	3.233
POLYDIMETHYL, METHYL VINYL SILOXANE DIMEVI TERMINATED	68083181	NOT DET.	NOT DET.	3.233
SILVER	7440-22-4	10mg/m3	.01mg/m3	3.2
C5-C6-RICH HYDROCARBONS	068476506	0.1 MG/M3	0.1 MG/M3	0.020
HEXAMETHYLDISILOXANE	000107460	NOT DET.	NOT DET.	2.200
SODA LIME GLASS	65997-17-3	10mg/m3	NL	50.1

THE ABOVE INFORMATION IS DEEMED RELIABLE AS FAR AS OUR SUPPLIERS POSITION ON REPORTING CONCENTRATIONS OF COMPONENTS IN THE MATERIALS THEY SUPPLY. THIS DATA IS OFFERED IN GOOD FAITH AND IS NOT INTENDED TO BE USED FOR PRODUCT SPECIFICATIONS.