

# RTV SILICONE

## 100% RTV Silicone

Pressure Pak Cans 7.25 oz.-8 oz.

### RTV 100 % SILICONE ADHESIVE SEALANT

is a nonslump paste-like, one part moisture cure material which has excellent resistance to extreme temperature, moisture, ozone, vibration, and weathering.

### FEATURES

- One-part silicone rubber sealant.
- Can be applied at temperatures from -35 F (-37 C) to 140 F (60 C).
- Will not crack or become brittle with age.
- Excellent adhesion to glass, most types of wood, metal ceramics, porcelain, silicone rubber, synthetic rubbers and many plastics.
- Available colors: Blue, Black, Red High Temp., Clear and White
- Oxygen Sensor Safe .

### APPLICATIONS

- Sealant and adhesive for many automotive applications.
- Formed in place gasketing.
- An adhesive sealant when high temperatures are a factor.
- An adhesive sealant for many marine applications.
- A trailer and recreation vehicle sealant.
- Sealing and adhering appliance parts.

### APPLICABLE STANDARDS

- RTV Silicone Adhesive Sealant meets or exceeds the requirements of the following specifications:
- TT-S-001543A (COM-NBS) Class A-Federal Specifications for Silicone Building Sealants.
- TT-S-00230C (COM-NBS) Class A, Non-Sag-Federal Specifications for One-Component Silicone Sealants.

### APPLICABLE STANDARDS CONTINUED

- ASTM C 920-79 - Standard Specification for Elastomeric Joint Sealant as Type S, Grade NS, Class 25, Use NT, G and A.
- CGSB 19GP9M (Canadian Government Specifications Board).
- RTV Silicone Adhesive Sealant is designed to meet the requirement of MIL -A-46106A. Amend 2, Type 1.

**Pressure Pak Cans are simply applied by pressing the nozzle on the top of the can. No caulking cartridge needed.**

Can Size: 7.25 oz.-8 oz.  
Cans/case: 12

Blue  
Clear  
Black  
White  
Red High Temp.

Moreau Marketing  
& Sales

336-764-5232  
Fax: 336-764-0941

